

Radiant Panel Flexible Hoses

Flexible hoses are used for connecting the mains pipework to the radiant panel and also to interconnect between 2 panels when installed in a run.

Features / Benefits

- BSRIA BG4-2004 approved
- Superior material selection to ensure longevity
- Easy to fit, helping reduce installation times
- Excellent abrasion and crush resistance
- Working pressure of 10 Bar @ 85°C
- SPC will calculate the number of hoses required for the panels required
- 5 different hoses as standard, bespoke lengths and end fittings available upon request
- Quick turnaround available

Standard offerings (In Stock)

Order Code	Fitting 1 (mm)	Fitting 2 (mm)	Length	Connection between:
33/860	12 – Push Fit	12 – Push Fit	400	Panel - Panel
33/862	15 – Push Fit	12 – Push Fit	750	Mains - Panel
33/874	15 – Compression	15 – Compression	750	Mains – Panel
33/873	15 – Compression	15 – Compression	400	Panel - Panel
33/882	15 – Push Fit	10 – Push Fit	750	Mains - Panel

Note: If you require different sizes than that stated above, please get in touch to discuss further.

Submittal information

Material:

Hose – 12mm Bore Elite EPDM lined hose

Braid – 304 Stainless Steel

Push Fit fitting – Nickel Plated Brass including collet with EPDM 'O' Ring

Compression Fitting – Nickel Plated Brass Nut with Brass Olive

End fittings are swaged in place using stainless steel ferrules



SPC House, Evington Valley Road, Leicester LE5 5LU

T: 0116 249 0044 E: spc@spc-hvac.co.uk

spc-hvac.co.uk

Ref: SPC Radiant Hoses